



Motordamper GFD-24

From $\varnothing 80$ mm to 250 mm

GEOVENT quickly turning on / off damper GFD-24 is specially designed for use in point extraction systems that require rapid opening and closing of the dampers by suction points. GFD-24 is a close damper that can open 90° down to 1 second. Rotating speed can be set between 1 to 10 seconds. This damper is also available with modulating motor for fume hoods and fume for accurate control of the air. The damper is available from $\varnothing 80$ mm to $\varnothing 250$ mm.

Power supply:	AC/DC 24 V +/- 10 %
Power consumption:	18 W
Wire dimmensions:	22 VA
Connection:	Cable, 1 m
Torque:	2,5 Nm
Angle of rotation:	90°
EMC-emission:	EN 50081-1
EMC-immunity:	EN 50082-1
Ambient temperature:	0 - 50 $^\circ\text{C}$
Protedtion class:	IP54
Sound power level:	Ca. 45 dB(A)



Ordering table for GFD-24

Art. no.	Descriptions
61-091	Motordamper GFD-24 - $\varnothing 80$ mm
61-092	Motordamper GFD-24 - $\varnothing 100$ mm
61-093	Motordamper GFD-24 - $\varnothing 125$ mm
61-094	Motordamper GFD-24 - $\varnothing 160$ mm
61-095	Motordamper GFD-24 - $\varnothing 200$ mm
61-096	Motordamper GFD-24 - $\varnothing 250$ mm
Accessories	
61-046	Power supply 230 V / 24 V for GFD motordamper