



GEOVENT

Portable Fan

PM - 180

GEOVENT portable fan PM-180-1 is suitable for extraction of welding fumes, vapors etc., where it is not possible to establish a stationary place for extraction. Furthermore it can be used for extraction from or air supply into cargo areas, containers, etc.

Delivered complete, ready to use, with 2 x 5 m \varnothing 125mm or \varnothing 160mm hose and aluminum hood with 1 magnet

A very suitable solution for use in the farming industry, traveling fitters or onboard ships. Perfect for situations where there is a requirement for quick & flexible extraction.



Electric data / Air data / Misc. data / Features

- 1x230V50/60Hz, 0,55 kW
- start/stop switch and circuit breaker 10A
- Air flow without hose: 1.400 m³/h
- Air flow with normal use of hose:
600 m³/h (\varnothing 125mm)
800 m³/h (\varnothing 160mm).
- Air flow with fully extended hose:
700 m³/h (\varnothing 125mm)
1.100 m³/h (\varnothing 160mm)
- Made of galvanized sheet metal with epoxy coated carrying bracket. All screws and bolts are electroplated.
- 2 x 5 m \varnothing 125mm or \varnothing 160 mm flexible and light-weight hose with socket fittings for easy on and off assembling.
- Epoxy coated hood with 1 heavy duty magnet.
- ABS-plastic handle for high mobility of fan.
- Art. No.: 30-006A (\varnothing 125mm)
30-006H (\varnothing 160mm)
- Weight: 19,3kg
- Sound level: 68dB(A)



GEOVENT

Portable Fan

PM - 180

